

Food Establishment Inspection Report



Wichita Falls - Wichita County
Public Health District
1700 Third Street
Wichita Falls, TX 76301
940-761-7800

SITE NO.	INV NO.	IR NO.	DATE	INSPECTION TIME	INSPECTOR
5630	1		01/26/2011		Baxter, Mike

SITE INFORMATION	INVENTORY/MANAGER	SERVICE TYPE/FREQUENCY
DELIGHTFUL DONUTS 3705 SHEPPARD ACCESS RD # B WICHITA FALLS TX 76306 940-851-7777	Process 2	Inspection- Regular Inspected 3 Times per Year

Scheduled calender inspections.

Violations: Critical - 1 Non-Critical - 3 Score: 97

CRITICAL VIOLATIONS SUMMARY

<u>CODE</u>	<u>DESCRIPTION</u>	<u>POINTS</u>	<u>CORRECTED</u>
21	Manual/Mechanical Warewashing & Sanitizing @ ____ ppm/Temp.	3	_____

NON-CRITICAL VIOLATIONS SUMMARY

<u>CODE</u>	<u>DESCRIPTION</u>	<u>POINTS</u>	<u>CORRECTED</u>
28	OTHER VIOLATIONS	0	_____
28	OTHER VIOLATIONS	0	_____
28	OTHER VIOLATIONS	0	_____

CRITICAL VIOLATIONS DETAIL

<u>CODE</u>	<u>DESCRIPTION</u>
21	<p>Texas Food Establishment Rules</p> <p>TFER 229.165(k) thru 229.165(y)</p> <p>The wash compartment of the sink shall, when used for washing, contain a wash solution mixed according to manufacturer's label instructions. The temperature of the wash solution shall be maintained at not less than 43 degrees C (110 degrees F) unless specified differently by the manufacturer of the washing agent. If a detergent-sanitizer is used without a hot water rinse, the same agent must be used in both the cleaning and sanitizing steps. A chemical sanitizer used in a sanitizing solution shall be used in accordance with</p>

CODE **DESCRIPTION**

EPA approved manufacturer's label use instructions. If hot water is used for sanitizing, the temperature of the water shall be maintained at 77 degrees C (171 degrees F) or above. Warewashing machines, manufacturers' operating instructions. A warewashing machine and its auxiliary components shall be operated in accordance with the machine's data plate and other manufacturer's instructions. A warewashing machine's conveyor speed or automatic cycle times shall be maintained accurately timed in accordance with manufacturer's specifications. Mechanical warewashing equipment, hot water sanitization temperatures. Except as specified in subparagraph (B) of this paragraph, in a mechanical operation, the temperature of the fresh hot water sanitizing rinse as it enters the manifold may not be more than 90 degrees Celsius (194 degrees Fahrenheit), or less than: for a stationary rack, single temperature machine, 74 degrees Celsius (165 degrees Fahrenheit); or for all other machines, 82 degrees Celsius (180 degrees Fahrenheit). The maximum temperature specified under subparagraph (A) of this paragraph does not apply to the high pressure and temperature systems with wand-type, hand-held spraying devices used for the in-place cleaning and sanitizing of equipment such as meat saws. Mechanical warewashing equipment, sanitization pressure. The flow pressure of the fresh hot water sanitizing rinse in a warewashing machine may not be less than 100 kilopascals (15 pounds per square inch) or more than 170 kilopascals (25 pounds per square inch) as measured in the water line immediately downstream or upstream from the fresh hot water sanitizing rinse control valve.

To Wit: No Test Strips

To Correct: Need Test Strips to check sanitizer level of sanitizer water

NON-CRITICAL VIOLATIONS DETAIL**CODE** **DESCRIPTION**

28 OTHER VIOLATIONS- REQUIRE CORRECTIVE ACTION , NOT TO EXCEED 90 DAYS OR NEXT INSPECTION, WHICHEVER COMES FIRST.

To Wit: damaged ceiling tiles

To Correct: Damaged ceiling tiles to be replaced

To Wit: household microwave

To Correct: Microwave is to be a commercial microwave.

To Wit: No children in the food area

To Correct: The owner has a 2 year old child which she watches all day. I explained to her she needs to arrange day care. and child cannot be there behind the counter.

I HEREBY, ACKNOWLEDGE THE ISSUANCE AND RECEIPT OF THIS OFFICIAL Food Establishment Inspection Report.

Mike Baxter, Public Health Officer

OWNER / MANAGER SIGNATURE

OWNER / MANAGER PRINT NAME