

# Food Establishment Inspection Report



Wichita Falls - Wichita County  
 Public Health District  
 1700 Third Street  
 Wichita Falls, TX 76301  
 940-761-7800

<b>SITE NO.</b>	<b>INV NO.</b>	<b>IR NO.</b>	<b>DATE</b>	<b>INSPECTION TIME</b>	<b>INSPECTOR</b>
3266	1		05/12/2011		McKenzie, Suzanne

<b>SITE INFORMATION</b>	<b>INVENTORY/MANAGER</b>	<b>SERVICE TYPE/FREQUENCY</b>
DOLLAR SAVER 114 EASTSIDE WICHITA FALLS TX 76301 940-766-2379	Process 2	Inspection- Regular Inspected 3 Times per Year

Scheduled calender inspections.

---

**Violations: Critical - 2 Score: 94**

---

### CRITICAL VIOLATIONS SUMMARY

<u>CODE</u>	<u>DESCRIPTION</u>	<u>POINTS</u>	<u>CORRECTED</u>
21	Manual/Mechanical Warewashing & Sanitizing @ ____ ppm/Temp.	3	05/12/2011
25	Food Contact Surfaces-Cleaned/Sanitized/Good Repair/Storage	3	05/12/2011

### CRITICAL VIOLATIONS DETAIL

<u>CODE</u>	<u>DESCRIPTION</u>
21	<p>Texas Food Establishment Rules</p> <p>TFER 229.165(k) thru 229.165(y)</p> <p>The wash compartment of the sink shall, when used for washing, contain a wash solution mixed according to manufacturer's label instructions. The temperature of the wash solution shall be maintained at not less than 43 degrees C (110 degrees F) unless specified differently by the manufacturer of the washing agent. If a detergent-sanitizer is used without a hot water rinse, the same agent must be used in both the cleaning and sanitizing steps. A chemical sanitizer used in a sanitizing solution shall be used in accordance with EPA approved manufacturer's label use instructions. If hot water is used for sanitizing, the temperature of the water shall be maintained at 77 degrees C (171 degrees F) or above. Warewashing machines, manufacturers' operating instructions.</p> <p>A warewashing machine and its auxiliary components shall be operated in accordance with the machine's data plate and other manufacturer's instructions.</p> <p>A warewashing machine's conveyor speed or automatic cycle times shall be maintained accurately timed in accordance with manufacturer's specifications. Mechanical warewashing equipment, hot water sanitization temperatures.</p> <p>Except as specified in subparagraph (B) of this paragraph, in a mechanical operation, the temperature of the fresh hot water sanitizing rinse as it enters the manifold may not be more than 90 degrees Celsius (194 degrees Fahrenheit), or less than:</p> <p>for a stationary rack, single temperature machine, 74 degrees Celsius (165 degrees</p>

<u>CODE</u>	<u>DESCRIPTION</u>
	<p>Fahrenheit); or  for all other machines, 82 degrees Celsius (180 degrees Fahrenheit).  The maximum temperature specified under subparagraph (A) of this paragraph does not apply to the high pressure and temperature systems with wand-type, hand-held spraying devices used for the in-place cleaning and sanitizing of equipment such as meat saws.  Mechanical warewashing equipment, sanitization pressure.  The flow pressure of the fresh hot water sanitizing rinse in a warewashing machine may not be less than 100 kilopascals (15 pounds per square inch) or more than 170 kilopascals (25 pounds per square inch) as measured in the water line immediately downstream or upstream from the fresh hot water sanitizing rinse control valve.</p>
To Wit:	A sink with at least three compartments is not provided for manually washing, rinsing and sanitizing equipment and utensils or a warewashing machine or alternative equipment has not been approved by the Health Authority. (Corrected 05/12/11)
To Correct:	A sink with at least three compartments shall be provided for manually washing, rinsing and sanitizing equipment and utensils unless a warewashing machine or alternative equipment has been approved by the Health Authority. Corrections must be made immediately.
25	<p>Page 76  §229.165(d)  (d) Cleanability.  (1) Food-contact surfaces. Multiuse food-contact surfaces shall be:  (A) smooth;  (B) free of breaks, open seams, cracks, chips, inclusions, pits, and similar imperfections;  (C) free of sharp internal angles, corners, and crevices;  (D) finished to have smooth welds and joints; and  (E) except as specified in subparagraph (B) of this paragraph, accessible for cleaning and inspection by one of the following methods:  (i) without being disassembled;  (ii) by disassembling without the use of tools; or  (iii) by easy disassembling with the use of handheld tools commonly available to maintenance and cleaning personnel such as screwdrivers, pliers, and wrenches.  (2) Paragraph (5) of this subsection does not apply to cooking oil storage tanks, distribution lines for cooking oils, or beverage syrup lines or tubes.  (3) Cleaned in place (CIP) equipment.  (A) CIP equipment shall meet the characteristics specified under paragraph (1) of this subsection and shall be designed and constructed so that:  (i) cleaning and sanitizing solutions circulate throughout a fixed system and contact all interior food-contact surfaces; and  (ii) the system is self-draining or capable of being completely drained of cleaning and sanitizing solutions; and</p>
To Wit:	The ice cream freezer and ice freezer needs to be defrosted, located in the food preparation area has adhering ice crystals. (Corrected 05/12/11)
To Correct:	The ice cream freezer and ice freezer needs to be defrosted, located in the food preparation area must be properly washed, rinsed and sanitized and free of ice crystals. Corrections must be made immediately.

I HEREBY, ACKNOWLEDGE THE ISSUANCE AND RECEIPT OF THIS OFFICIAL Food Establishment Inspection Report.

\_\_\_\_\_  
Suzanne McKenzie, PUBLIC HEALTH OFFICER

\_\_\_\_\_  
OWNER / MANAGER SIGNATURE

\_\_\_\_\_  
OWNER / MANAGER PRINT NAME