

Food Establishment Inspection Report



Wichita Falls - Wichita County
Public Health District
1700 Third Street
Wichita Falls, TX 76301
940-761-7800

SITE NO. 201 **INV NO.** 1 **IR NO.** **DATE** 04/19/2011 **INSPECTION TIME** **INSPECTOR** Baxter, Mike

SITE INFORMATION

EL NORTENO
110 N BURNETT
WICHITA FALLS TX 76306
940-767-9745

INVENTORY/MANAGER

Process 3

SERVICE TYPE/FREQUENCY

Inspection- Regular
Inspected 4 Times per Year

Scheduled calendar inspections.

Violations: Critical - 4 Non-Critical - 6 Score: 88

CRITICAL VIOLATIONS SUMMARY

<u>CODE</u>	<u>DESCRIPTION</u>	<u>POINTS</u>	<u>CORRECTED</u>
17	Handwash Facilities with Soap & Towels	3	_____
21	Manual/Mechanical Warewashing & Sanitizing @ ____ ppm/Temp.	3	_____
24	Thermometers Provided/Accurate/Properly Calibrated +/- 2 F	3	_____
25	Food Contact Surfaces-Cleaned/Sanitized/Good Repair/Storage	3	_____

NON-CRITICAL VIOLATIONS SUMMARY

<u>CODE</u>	<u>DESCRIPTION</u>	<u>POINTS</u>	<u>CORRECTED</u>
28	OTHER VIOLATIONS	0	_____
28	OTHER VIOLATIONS	0	_____
28	OTHER VIOLATIONS	0	_____
28	OTHER VIOLATIONS	0	_____
28	OTHER VIOLATIONS	0	_____
28	OTHER VIOLATIONS	0	_____

CRITICAL VIOLATIONS DETAIL

<u>CODE</u>	<u>DESCRIPTION</u>
17	<p>Texas Food Establishment Rules</p> <p>Page 122 §229.167 (e) Handwashing facilities. (1) Minimum number. Handwashing facilities shall be provided as specified under §229.166(g)(1) of this title.</p> <p>(2) Handwashing cleanser, availability. Each handwashing lavatory or group of 2 adjacent lavatories shall be provided with a supply of hand cleaning liquid, powder, or bar soap.</p> <p>(3) Hand drying provision. Each handwashing lavatory or group of adjacent lavatories shall be provided with: (A) individual, disposable towels; (B) a continuous towel system that supplies the user with a clean towel; or (C) a heated-air hand drying device.</p> <p>To Wit: no towels at the hand wash sink</p>
21	<p>Texas Food Establishment Rules</p> <p>TFER 229.165(k) thru 229.165(y) The wash compartment of the sink shall, when used for washing, contain a wash solution mixed according to manufacturer's label instructions. The temperature of the wash solution shall be maintained at not less than 43 degrees C (110 degrees F) unless specified differently by the manufacturer of the washing agent. If a detergent-sanitizer is used without a hot water rinse, the same agent must be used in both the cleaning and sanitizing steps. A chemical sanitizer used in a sanitizing solution shall be used in accordance with EPA approved manufacturer's label use instructions. If hot water is used for sanitizing, the temperature of the water shall be maintained at 77 degrees C (171 degrees F) or above. Warewashing machines, manufacturers' operating instructions. A warewashing machine and its auxiliary components shall be operated in accordance with the machine's data plate and other manufacturer's instructions. A warewashing machine's conveyor speed or automatic cycle times shall be maintained accurately timed in accordance with manufacturer's specifications. Mechanical warewashing equipment, hot water sanitization temperatures. Except as specified in subparagraph (B) of this paragraph, in a mechanical operation, the temperature of the fresh hot water sanitizing rinse as it enters the manifold may not be more than 90 degrees Celsius (194 degrees Fahrenheit), or less than: for a stationary rack, single temperature machine, 74 degrees Celsius (165 degrees Fahrenheit); or for all other machines, 82 degrees Celsius (180 degrees Fahrenheit). The maximum temperature specified under subparagraph (A) of this paragraph does not apply to the high pressure and temperature systems with wand-type, hand-held spraying devices used for the in-place cleaning and sanitizing of equipment such as meat saws. Mechanical warewashing equipment, sanitization pressure. The flow pressure of the fresh hot water sanitizing rinse in a warewashing machine may not be less than 100 kilopascals (15 pounds per square inch) or more than 170 kilopascals (25 pounds per square inch) as measured in the water line immediately downstream or upstream from the fresh hot water sanitizing rinse control valve.</p>

<u>CODE</u>	<u>DESCRIPTION</u>
-------------	--------------------

To Wit:	no test strips
To Correct:	Need test strips to check sanitizer level of the water for sanitizing dishes after washing
24	<p>Page 77</p> <p>§229.165(e)</p> <p>(e) Accuracy of temperature measuring devices, food.</p> <p>(1) Temperature measuring device, food.</p> <p>(A) Food temperature measuring device that are scaled only in Celsius or dually scaled in Celsius and Fahrenheit shall be accurate to ± 1 degrees Celsius in the intended range of use.</p> <p>(B) Food temperature measuring device that are scaled only in Fahrenheit shall be accurate to ± 2 degrees Fahrenheit in the intended range of use.</p> <p>(2) Temperature measuring devices, ambient air and water.</p> <p>#24</p> <p>78</p> <p>§229.165(e) §229.165(f)</p> <p>(A) Ambient air and water temperature measuring device that are scaled in Celsius or dually scaled in Celsius and Fahrenheit shall be designed to be easily readable and accurate to ± 1.5 degrees Celsius in the intended range of use.</p> <p>(B) Ambient air and water temperature measuring device that are scaled only in Fahrenheit shall be accurate to ± 3 degrees Fahrenheit in the intended range of use.</p>
To Wit:	no thermometers in reach in refrigerators
To Correct:	All refrigerators are to have thermometers.
25	<p>Page 76</p> <p>§229.165(d)</p> <p>(d) Cleanability.</p> <p>(1) Food-contact surfaces. Multiuse food-contact surfaces shall be:</p> <p>(A) smooth;</p> <p>(B) free of breaks, open seams, cracks, chips, inclusions, pits, and similar imperfections;</p> <p>(C) free of sharp internal angles, corners, and crevices;</p> <p>(D) finished to have smooth welds and joints; and</p> <p>(E) except as specified in subparagraph (B) of this paragraph, accessible for cleaning and inspection by one of the following methods:</p> <p>(i) without being disassembled;</p> <p>(ii) by disassembling without the use of tools; or</p> <p>(iii) by easy disassembling with the use of handheld tools commonly available to maintenance and cleaning personnel such as screwdrivers, pliers, and wrenches.</p> <p>(2) Paragraph (5) of this subsection does not apply to cooking oil storage tanks, distribution lines for cooking oils, or beverage syrup lines or tubes.</p> <p>(3) Cleaned in place (CIP) equipment.</p> <p>(A) CIP equipment shall meet the characteristics specified under paragraph (1) of this subsection and shall be designed and constructed so that:</p> <p>(i) cleaning and sanitizing solutions circulate throughout a fixed system and contact all interior food-contact surfaces; and</p> <p>(ii) the system is self-draining or capable of being completely drained of cleaning and</p>

<u>CODE</u>	<u>DESCRIPTION</u>
	sanitizing solutions; and
To Wit:	microwave dirty
To Correct:	corrected

NON-CRITICAL VIOLATIONS DETAIL

<u>CODE</u>	<u>DESCRIPTION</u>
28	OTHER VIOLATIONS- REQUIRE CORRECTIVE ACTION , NOT TO EXCEED 90 DAYS OR NEXT INSPECTION, WHICHEVER COMES FIRST.
To Wit:	the refrigerator under prep table needs seal repaired
To Correct:	The seal on the reach in refrigerator under the prep table is sagging and needs to be replaced or repaired.
To Wit:	broken missing handle on refrigerator door
To Correct:	The broken and missing handle on the reach in refrigerator door needs to be repaired.
To Wit:	household microwave
To Correct:	The microwave needs to be replaced with a commercial microwave
To Wit:	broken glass on reach in refrigerator door
To Correct:	The broken glass on the refrigerator door is repaired with duct tape. It should be replaced with new glass
To Wit:	wall by 3 comp sink is badly damaged
To Correct:	The wall behind and beside the 3 comp sink is badly damaged and is to be repaired
To Wit:	shelf above 3 comp sink needs sealing and repainted
To Correct:	Shelf above 3 comp sink needs to be sealed and repainted or replaced.

I HEREBY, ACKNOWLEDGE THE ISSUANCE AND RECEIPT OF THIS OFFICIAL Food Establishment Inspection Report.

Mike Baxter, Public Health Officer

OWNER / MANAGER SIGNATURE

OWNER / MANAGER PRINT NAME