

# Food Establishment Inspection Report



Wichita Falls - Wichita County  
Public Health District  
1700 Third Street  
Wichita Falls, TX 76301  
940-761-7800

SITE NO.	INV NO.	IR NO.	DATE	INSPECTION TIME	INSPECTOR
6618	1		02/04/2010		O'Neal, Robbie

SITE INFORMATION	INVENTORY/MANAGER	SERVICE TYPE/FREQUENCY
HAVEN RED RIVER , LLC 1505 8TH ST WICHITA FALLS TX 76301 940-322-3171	Process 3	Permit Inspection Permit Granted Inspected 4 Times per Year

---

**Violations: Critical - 3 Non-Critical - 2 Score: 91**

---

## CRITICAL VIOLATIONS SUMMARY

<u>CODE</u>	<u>DESCRIPTION</u>	<u>POINTS</u>	<u>CORRECTED</u>
16	Handwash Facilities Adequate & Access	3	_____
21	Manual/Mechanical Warewashing & Sanitizing @ ____ ppm/Temp.	3	02/04/2010
25	Food Contact Surfaces-Cleaned/Sanitized/Good Repair/Storage	3	_____

## NON-CRITICAL VIOLATIONS SUMMARY

<u>CODE</u>	<u>DESCRIPTION</u>	<u>POINTS</u>	<u>CORRECTED</u>
28	OTHER VIOLATIONS	0	_____
28	OTHER VIOLATIONS	0	_____

## CRITICAL VIOLATIONS DETAIL

<u>CODE</u>	<u>DESCRIPTION</u>
16	Texas Food Establishment Rules  Page 107 §229.166 (h) Plumbing, location and placement. (1) Handwashing facilities. A handwashing facility shall be located: (A) to allow convenient use by employees in food preparation, food dispensing, and warewashing areas; and

**CODE**                      **DESCRIPTION**

(B) in, or immediately adjacent to, toilet rooms.

To Wit:                      drain pipe leaking

21                              Texas Food Establishment Rules

TFER 229.165(k) thru 229.165(y)

The wash compartment of the sink shall, when used for washing, contain a wash solution mixed according to manufacturer's label instructions. The temperature of the wash solution shall be maintained at not less than 43 degrees C (110 degrees F) unless specified differently by the manufacturer of the washing agent. If a detergent-sanitizer is used without a hot water rinse, the same agent must be used in both the cleaning and sanitizing steps. A chemical sanitizer used in a sanitizing solution shall be used in accordance with EPA approved manufacturer's label use instructions. If hot water is used for sanitizing, the temperature of the water shall be maintained at 77 degrees C (171 degrees F) or above. Warewashing machines, manufacturers' operating instructions. A warewashing machine and its auxiliary components shall be operated in accordance with the machine's data plate and other manufacturer's instructions.

A warewashing machine's conveyor speed or automatic cycle times shall be maintained accurately timed in accordance with manufacturer's specifications. Mechanical warewashing equipment, hot water sanitization temperatures.

Except as specified in subparagraph (B) of this paragraph, in a mechanical operation, the temperature of the fresh hot water sanitizing rinse as it enters the manifold may not be more than 90 degrees Celsius (194 degrees Fahrenheit), or less than:

for a stationary rack, single temperature machine, 74 degrees Celsius (165 degrees Fahrenheit); or

for all other machines, 82 degrees Celsius (180 degrees Fahrenheit).

The maximum temperature specified under subparagraph (A) of this paragraph does not apply to the high pressure and temperature systems with wand-type, hand-held spraying devices used for the in-place cleaning and sanitizing of equipment such as meat saws. Mechanical warewashing equipment, sanitization pressure.

The flow pressure of the fresh hot water sanitizing rinse in a warewashing machine may not be less than 100 kilopascals (15 pounds per square inch) or more than 170 kilopascals (25 pounds per square inch) as measured in the water line immediately downstream or upstream from the fresh hot water sanitizing rinse control valve.

To Wit:                      The detergent-sanitizer combination agent used as the sanitizer in the dishwasher area is at an inadequate concentration of < 50 PPM to sanitize equipment and utensils. (Corrected 02/04/10)

To Correct:                The detergent-sanitizer combination agent used as the sanitizer in the dishwasher area must be at a concentration of > 50ppm bleach or >200 ppm quaternary ammonium compound to sanitize equipment and utensils. Corrections must be made immediately.

25                              Page 76

§229.165(d)

(d) Cleanability.

(1) Food-contact surfaces. Multiuse food-contact surfaces shall be:

(A) smooth;

(B) free of breaks, open seams, cracks, chips, inclusions, pits, and similar imperfections;

(C) free of sharp internal angles, corners, and crevices;

(D) finished to have smooth welds and joints; and

**CODE                      DESCRIPTION**

(E) except as specified in subparagraph (B) of this paragraph, accessible for cleaning and inspection by one of the following methods:

- (i) without being disassembled;
- (ii) by disassembling without the use of tools; or
- (iii) by easy disassembling with the use of handheld tools commonly available to maintenance and cleaning personnel such as screwdrivers, pliers, and wrenches.

(2) Paragraph (5) of this subsection does not apply to cooking oil storage tanks, distribution lines for cooking oils, or beverage syrup lines or tubes.

(3) Cleaned in place (CIP) equipment.

(A) CIP equipment shall meet the characteristics specified under paragraph (1) of this subsection and shall be designed and constructed so that:

- (i) cleaning and sanitizing solutions circulate throughout a fixed system and contact all interior food-contact surfaces; and
- (ii) the system is self-draining or capable of being completely drained of cleaning and sanitizing solutions; and

To Wit:                      The seals located in the kitchen has adhering foreign material.

To Correct:                The seals located in the kitchen must be properly washed, rinsed and sanitized and free of foreign material. Corrections must be made immediately.

**NON-CRITICAL VIOLATIONS DETAIL**

**CODE                      DESCRIPTION**

28                              OTHER VIOLATIONS- REQUIRE CORRECTIVE ACTION , NOT TO EXCEED 90 DAYS OR NEXT INSPECTION, WHICHEVER COMES FIRST.

To Wit:                      lights must be shielded in store room.

To Wit:                      need to clean floor behind grill area.

**I HEREBY, ACKNOWLEDGE THE ISSUANCE AND RECEIPT OF THIS OFFICIAL Food Establishment Inspection Report.**

\_\_\_\_\_  
**Robbie O'Neal, Public Health Inspector II**

\_\_\_\_\_  
**OWNER / MANAGER SIGNATURE**

\_\_\_\_\_  
**OWNER / MANAGER PRINT NAME**