

Food Establishment Inspection Report



Wichita Falls - Wichita County
Public Health District
1700 Third Street
Wichita Falls, TX 76301
940-761-7800

SITE NO. 4937 **INV NO.** 3 **IR NO.** **DATE** 09/21/2011 **INSPECTION TIME** **INSPECTOR** O'Neal, Robbie

SITE INFORMATION
HOMEWOOD SUITES BY HILTON
2675 PLAZA PARKWAY
WICHITA FALLS TX 76308
940-691-4663 Fax 940-691-4664

INVENTORY/MANAGER
Process 3

SERVICE TYPE/FREQUENCY
Inspection- Regular
Inspected 4 Times per Year

Scheduled calendar inspections.

Violations: Critical - 2 Score: 94

CRITICAL VIOLATIONS SUMMARY

<u>CODE</u>	<u>DESCRIPTION</u>	<u>POINTS</u>	<u>CORRECTED</u>
17	Handwash Facilities with Soap & Towels	3	_____
21	Manual/Mechanical Warewashing & Sanitizing @ ____ ppm/Temp.	3	_____

CRITICAL VIOLATIONS DETAIL

<u>CODE</u>	<u>DESCRIPTION</u>
17	Texas Food Establishment Rules Page 122 §229.167 (e) Handwashing facilities. (1) Minimum number. Handwashing facilities shall be provided as specified under §229.166(g)(1) of this title. (2) Handwashing cleanser, availability. Each handwashing lavatory or group of 2 adjacent lavatories shall be provided with a supply of hand cleaning liquid, powder, or bar soap. (3) Hand drying provision. Each handwashing lavatory or group of adjacent lavatories shall be provided with: (A) individual, disposable towels; (B) a continuous towel system that supplies the user with a clean towel; or (C) a heated-air hand drying device.

To Wit: No hand drying provisions were available at the handwash facilities in the kitchen.

<u>CODE</u>	<u>DESCRIPTION</u>
-------------	--------------------

To Correct: Hand drying provisions must be available at the handwash facilities in the kitchen. Corrections must be made immediately.

21 Texas Food Establishment Rules

TFER 229.165(k) thru 229.165(y)

The wash compartment of the sink shall, when used for washing, contain a wash solution mixed according to manufacturer's label instructions. The temperature of the wash solution shall be maintained at not less than 43 degrees C (110 degrees F) unless specified differently by the manufacturer of the washing agent. If a detergent-sanitizer is used without a hot water rinse, the same agent must be used in both the cleaning and sanitizing steps. A chemical sanitizer used in a sanitizing solution shall be used in accordance with EPA approved manufacturer's label use instructions. If hot water is used for sanitizing, the temperature of the water shall be maintained at 77 degrees C (171 degrees F) or above. Warewashing machines, manufacturers' operating instructions.

A warewashing machine and its auxiliary components shall be operated in accordance with the machine's data plate and other manufacturer's instructions.

A warewashing machine's conveyor speed or automatic cycle times shall be maintained accurately timed in accordance with manufacturer's specifications. Mechanical warewashing equipment, hot water sanitization temperatures.

Except as specified in subparagraph (B) of this paragraph, in a mechanical operation, the temperature of the fresh hot water sanitizing rinse as it enters the manifold may not be more than 90 degrees Celsius (194 degrees Fahrenheit), or less than:

for a stationary rack, single temperature machine, 74 degrees Celsius (165 degrees Fahrenheit); or

for all other machines, 82 degrees Celsius (180 degrees Fahrenheit).

The maximum temperature specified under subparagraph (A) of this paragraph does not apply to the high pressure and temperature systems with wand-type, hand-held spraying devices used for the in-place cleaning and sanitizing of equipment such as meat saws. Mechanical warewashing equipment, sanitization pressure.

The flow pressure of the fresh hot water sanitizing rinse in a warewashing machine may not be less than 100 kilopascals (15 pounds per square inch) or more than 170 kilopascals (25 pounds per square inch) as measured in the water line immediately downstream or upstream from the fresh hot water sanitizing rinse control valve.

To Wit: The bleach used as the sanitizer in the kitchen is at an inadequate concentration of < 50 PPM to sanitize equipment and utensils.

To Correct: The bleach used as the sanitizer in the kitchen must be at a concentration of > 50ppm bleach or >200 ppm quaterinary ammonium compound to sanitize equipment and utensils. Corrections must be made immediately.

I HEREBY, ACKNOWLEDGE THE ISSUANCE AND RECEIPT OF THIS OFFICIAL Food Establishment Inspection Report.

Robbie O'Neal, Public Health Officer

OWNER / MANAGER SIGNATURE

OWNER / MANAGER PRINT NAME