

Food Establishment Inspection Report

Wichita Falls - Wichita County
Public Health District
1700 Third Street
Wichita Falls, TX 76301
940-761-7800

SITE NO. 714 **INV NO.** 2 **IR NO.** **DATE** 02/03/2010 **INSPECTION TIME** **INSPECTOR** Railsback, Brian

SITE INFORMATION
KAMAY Y CONVENIENCE
8682 SEYMOUR HWY
WICHITA FALLS TX 76310
940-692-1581

INVENTORY/MANAGER
Deli

SERVICE TYPE/FREQUENCY
Inspection- Regular
Inspected 2 Times per Year

Violations: Critical - 3 Non-Critical - 2 Score: 91

CRITICAL VIOLATIONS SUMMARY

CODE	DESCRIPTION	POINTS	CORRECTED
16	Handwash Facilities Adequate & Access	3	_____
21	Manual/Mechanical Warewashing & Sanitizing @ ____ ppm/Temp.	3	_____
24	Thermometers Provided/Accurate/Properly Calibrated +/- 2 F	3	02/03/2010

NON-CRITICAL VIOLATIONS SUMMARY

CODE	DESCRIPTION	POINTS	CORRECTED
28	OTHER VIOLATIONS	0	_____
28	OTHER VIOLATIONS	0	_____

CRITICAL VIOLATIONS DETAIL

CODE	DESCRIPTION
16	Texas Food Establishment Rules Page 107 §229.166 (h) Plumbing, location and placement. (1) Handwashing facilities. A handwashing facility shall be located: (A) to allow convenient use by employees in food preparation, food dispensing, and warewashing areas; and

<u>CODE</u>	<u>DESCRIPTION</u>
	(B) in, or immediately adjacent to, toilet rooms.
To Wit:	There are inadequate handwashing sinks available in the kitchen.
To Correct:	There must be adequate handwashing sinks available in the kitchen. Corrections must be made within 90 days.
21	<p>Texas Food Establishment Rules</p> <p>TFER 229.165(k) thru 229.165(y)</p> <p>The wash compartment of the sink shall, when used for washing, contain a wash solution mixed according to manufacturer's label instructions. The temperature of the wash solution shall be maintained at not less than 43 degrees C (110 degrees F) unless specified differently by the manufacturer of the washing agent. If a detergent-sanitizer is used without a hot water rinse, the same agent must be used in both the cleaning and sanitizing steps. A chemical sanitizer used in a sanitizing solution shall be used in accordance with EPA approved manufacturer's label use instructions. If hot water is used for sanitizing, the temperature of the water shall be maintained at 77 degrees C (171 degrees F) or above. Warewashing machines, manufacturers' operating instructions. A warewashing machine and its auxiliary components shall be operated in accordance with the machine's data plate and other manufacturer's instructions. A warewashing machine's conveyor speed or automatic cycle times shall be maintained accurately timed in accordance with manufacturer's specifications. Mechanical warewashing equipment, hot water sanitization temperatures. Except as specified in subparagraph (B) of this paragraph, in a mechanical operation, the temperature of the fresh hot water sanitizing rinse as it enters the manifold may not be more than 90 degrees Celsius (194 degrees Fahrenheit), or less than: for a stationary rack, single temperature machine, 74 degrees Celsius (165 degrees Fahrenheit); or for all other machines, 82 degrees Celsius (180 degrees Fahrenheit). The maximum temperature specified under subparagraph (A) of this paragraph does not apply to the high pressure and temperature systems with wand-type, hand-held spraying devices used for the in-place cleaning and sanitizing of equipment such as meat saws. Mechanical warewashing equipment, sanitization pressure. The flow pressure of the fresh hot water sanitizing rinse in a warewashing machine may not be less than 100 kilopascals (15 pounds per square inch) or more than 170 kilopascals (25 pounds per square inch) as measured in the water line immediately downstream or upstream from the fresh hot water sanitizing rinse control valve.</p>
To Wit:	A sink with at least three compartments is not provided for manually washing, rinsing and sanitizing equipment and utensils or a warewashing machine or alternative equipment has not been approved by the Health Authority.
To Correct:	A sink with at least three compartments shall be provided for manually washing, rinsing and sanitizing equipment and utensils unless a warewashing machine or alternative equipment has been approved by the Health Authority. Corrections must be made immediately.
	Need test strips to check sanitizer levels in 3 compartment sink
24	<p>Page 77</p> <p>§229.165(e)</p> <p>(e) Accuracy of temperature measuring devices, food.</p>

<u>CODE</u>	<u>DESCRIPTION</u>
	(1) Temperature measuring device, food. (A) Food temperature measuring device that are scaled only in Celsius or dually scaled in Celsius and Fahrenheit shall be accurate to ±1 degrees Celsius in the intended range of use. (B) Food temperature measuring device that are scaled only in Fahrenheit shall be accurate to ±2 degrees Fahrenheit in the intended range of use. (2) Temperature measuring devices, ambient air and water. #24 78 §229.165(e) §229.165(f) (A) Ambient air and water temperature measuring device that are scaled in Celsius or dually scaled in Celsius and Fahrenheit shall be designed to be easily readable and accurate to ±1.5 degrees Celsius in the intended range of use. (B) Ambient air and water temperature measuring device that are scaled only in Fahrenheit shall be accurate to ±3 degrees Fahrenheit in the intended range of use.
To Wit:	The reachin refrigerator and freezer in the kitchen did not have a readily available and visible thermometer. (Corrected 02/03/10)
To Correct:	The reachin refrigerator and freezer in the kitchen must have a readily available and visible thermometer. Corrections must be made within 14 days.

NON-CRITICAL VIOLATIONS DETAIL

<u>CODE</u>	<u>DESCRIPTION</u>
28	OTHER VIOLATIONS- REQUIRE CORRECTIVE ACTION , NOT TO EXCEED 90 DAYS OR NEXT INSPECTION, WHICHEVER COMES FIRST.
To Wit:	No mop sink
To Correct:	Must install mop sink for cleaning of mops and dumping of water
To Wit:	Freezer and refrigerator are not commercial grade, will have to change them to commercial grade when they need replaced.

I HEREBY, ACKNOWLEDGE THE ISSUANCE AND RECEIPT OF THIS OFFICIAL Food Establishment Inspection Report.

 Brian Railsback, Public Health Officer

 OWNER / MANAGER SIGNATURE

 OWNER / MANAGER PRINT NAME