

# Food Establishment Inspection Report



Wichita Falls - Wichita County  
Public Health District  
1700 Third Street  
Wichita Falls, TX 76301  
940-761-7800

**SITE NO.** 580    **INV NO.** 5    **IR NO.**    **DATE** 04/29/2011    **INSPECTION TIME**    **INSPECTOR** Baxter, Mike

**SITE INFORMATION**

VFW #2147  
3305 SHEPPARD ACCESS  
WICHITA FALLS TX 76306  
940-855-0442

**INVENTORY/MANAGER**

Process 2 - Exempt

**SERVICE TYPE/FREQUENCY**

Inspection- Regular  
Inspected 3 Times per Year

Scheduled calendar inspections.

---

---

**Violations: Critical - 4 Non-Critical - 2 Score: 88**

---

---

**CRITICAL VIOLATIONS SUMMARY**

<b><u>CODE</u></b>	<b><u>DESCRIPTION</u></b>	<b><u>POINTS</u></b>	<b><u>CORRECTED</u></b>
21	Manual/Mechanical Warewashing & Sanitizing @ ____ ppm/Temp.	3	_____
24	Thermometers Provided/Accurate/Properly Calibrated +/- 2 F	3	_____
25	Food Contact Surfaces-Cleaned/Sanitized/Good Repair/Storage	3	_____
26	Posting Consumer Advisories- Heimlich/Raw Shellfish/Bufferet	3	_____

---

---

**NON-CRITICAL VIOLATIONS SUMMARY**

<b><u>CODE</u></b>	<b><u>DESCRIPTION</u></b>	<b><u>POINTS</u></b>	<b><u>CORRECTED</u></b>
28	OTHER VIOLATIONS	0	_____
28	OTHER VIOLATIONS	0	_____

---

---

**CRITICAL VIOLATIONS DETAIL**

<b><u>CODE</u></b>	<b><u>DESCRIPTION</u></b>
21	Texas Food Establishment Rules  TFER 229.165(k) thru 229.165(y) The wash compartment of the sink shall, when used for washing, contain a wash solution mixed according to manufacturer's label instructions. The temperature of the wash solution shall be maintained at not less than 43 degrees C (110 degrees F) unless specified

**CODE****DESCRIPTION**

differently by the manufacturer of the washing agent. If a detergent-sanitizer is used without a hot water rinse, the same agent must be used in both the cleaning and sanitizing steps. A chemical sanitizer used in a sanitizing solution shall be used in accordance with EPA approved manufacturer's label use instructions. If hot water is used for sanitizing, the temperature of the water shall be maintained at 77 degrees C (171 degrees F) or above. Warewashing machines, manufacturers' operating instructions.

A warewashing machine and its auxiliary components shall be operated in accordance with the machine's data plate and other manufacturer's instructions.

A warewashing machine's conveyor speed or automatic cycle times shall be maintained accurately timed in accordance with manufacturer's specifications. Mechanical warewashing equipment, hot water sanitization temperatures.

Except as specified in subparagraph (B) of this paragraph, in a mechanical operation, the temperature of the fresh hot water sanitizing rinse as it enters the manifold may not be more than 90 degrees Celsius (194 degrees Fahrenheit), or less than:

for a stationary rack, single temperature machine, 74 degrees Celsius (165 degrees Fahrenheit); or

for all other machines, 82 degrees Celsius (180 degrees Fahrenheit).

The maximum temperature specified under subparagraph (A) of this paragraph does not apply to the high pressure and temperature systems with wand-type, hand-held spraying devices used for the in-place cleaning and sanitizing of equipment such as meat saws. Mechanical warewashing equipment, sanitization pressure.

The flow pressure of the fresh hot water sanitizing rinse in a warewashing machine may not be less than 100 kilopascals (15 pounds per square inch) or more than 170 kilopascals (25 pounds per square inch) as measured in the water line immediately downstream or upstream from the fresh hot water sanitizing rinse control valve.

To Wit: no test strips for checking sanitizer water for dish washing

24 Page 77  
 §229.165(e)  
 (e) Accuracy of temperature measuring devices, food.  
 (1) Temperature measuring device, food.  
 (A) Food temperature measuring device that are scaled only in Celsius or dually scaled in Celsius and Fahrenheit shall be accurate to  $\pm 1$  degrees Celsius in the intended range of use.  
 (B) Food temperature measuring device that are scaled only in Fahrenheit shall be accurate to  $\pm 2$  degrees Fahrenheit in the intended range of use.  
 (2) Temperature measuring devices, ambient air and water.

#24

78

§229.165(e) §229.165(f)  
 (A) Ambient air and water temperature measuring device that are scaled in Celsius or dually scaled in Celsius and Fahrenheit shall be designed to be easily readable and accurate to  $\pm 1.5$  degrees Celsius in the intended range of use.  
 (B) Ambient air and water temperature measuring device that are scaled only in Fahrenheit shall be accurate to  $\pm 3$  degrees Fahrenheit in the intended range of use.

To Wit: no thermometers in refrigerator

25 Page 76  
 §229.165(d)  
 (d) Cleanability.

<u>CODE</u>	<u>DESCRIPTION</u>
	<p>(1) Food-contact surfaces. Multiuse food-contact surfaces shall be:</p> <p>(A) smooth;</p> <p>(B) free of breaks, open seams, cracks, chips, inclusions, pits, and similar imperfections;</p> <p>(C) free of sharp internal angles, corners, and crevices;</p> <p>(D) finished to have smooth welds and joints; and</p> <p>(E) except as specified in subparagraph (B) of this paragraph, accessible for cleaning and inspection by one of the following methods:</p> <p>(i) without being disassembled;</p> <p>(ii) by disassembling without the use of tools; or</p> <p>(iii) by easy disassembling with the use of handheld tools commonly available to maintenance and cleaning personnel such as screwdrivers, pliers, and wrenches.</p> <p>(2) Paragraph (5) of this subsection does not apply to cooking oil storage tanks, distribution lines for cooking oils, or beverage syrup lines or tubes.</p> <p>(3) Cleaned in place (CIP) equipment.</p> <p>(A) CIP equipment shall meet the characteristics specified under paragraph (1) of this subsection and shall be designed and constructed so that:</p> <p>(i) cleaning and sanitizing solutions circulate throughout a fixed system and contact all interior food-contact surfaces; and</p> <p>(ii) the system is self-draining or capable of being completely drained of cleaning and sanitizing solutions; and</p>
To Wit:	dirty counters and work table by stove
To Correct:	Wooden table by stove to be removed . Wooden table is dirty and to be removed
26	<p>Pages 37, 55 &amp;154</p> <p>229.164(h); (r) &amp; 173(b) -</p> <p>A card, sign or other effective means of notification shall be displayed to notify customers that clean tableware is to be used upon return to self-service areas. Food establishments which deliver shellfish to a consumer for raw consumption shall inform consumers of the significantly increased risk associated with certain especially vulnerable consumers eating such shellfish in raw or undercooked form. The Heimlich Maneuver Poster shall be in all food service establishments in a place conspicuous to employees or customers.</p>
To Wit:	no heimlich poster
To Correct:	Did give them 2 posters

### NON-CRITICAL VIOLATIONS DETAIL

<u>CODE</u>	<u>DESCRIPTION</u>
28	OTHER VIOLATIONS- REQUIRE CORRECTIVE ACTION , NOT TO EXCEED 90 DAYS OR NEXT INSPECTION, WHICHEVER COMES FIRST.
To Wit:	Damaged and missing ceiling tiles in kitchen tiles
To Correct:	The ceiling tiles are badly damaged and some missing. These are to be replaced ASAP

**CODE**            **DESCRIPTION**

To Wit:            microwave is household grade

To Correct:      The microwave is to be commercial grade

---

---

**I HEREBY, ACKNOWLEDGE THE ISSUANCE AND RECEIPT OF THIS OFFICIAL Food Establishment Inspection Report.**

\_\_\_\_\_  
**Mike Baxter, Public Health Officer**

\_\_\_\_\_  
**OWNER / MANAGER SIGNATURE**

\_\_\_\_\_  
**OWNER / MANAGER PRINT NAME**